


LT Series

Constant Voltage LED Driver

Features:

- Independent super slim design
- Analogue flicker-free
- Captured terminal screws
- Protections: opencircuit, shortcircuit, overload, overtemperature
- SELV equivalent
- Protection class II



Parameters:

Model No.	Input voltage (V)	Max. output (W)	Output voltage (V)	Output current (A)	Power factor (λ)	Efficiency full load (%)	No-load (W)	Ambient temperature t_a (°C)	Max. casing temperature t_c (°C)	Isolation	Dimensions LxWxH (mm)	Weight (g)
LT-30-12	220-240	30	12	0-2.5	0.95	85	<0.5	-20...+40	90	SELV	251x30x16	124
LT-30-24	220-240	30	24	0-1.25	0.95	86	<0.5	-20...+40	90	SELV	251x30x16	124
LT-45-12	220-240	45	12	0-3.75	0.95	86	<0.5	-20...+40	90	SELV	251x30x16	124
LT-45-24	220-240	45	24	0-1.87	0.95	87	<0.5	-20...+50	90	SELV	251x30x16	124
LT-60-12	220-240	60	12	0-5.0	0.95	90	<0.5	-20...+40	90	SELV	305x30x18.2	152
LT-60-24	220-240	60	24	0-2.5	0.95	90	<0.5	-20...+50	75	SELV	305x30x18.2	152
LT-60-48	220-240	60	48	0-1.25	0.95	90	<0.5	-20...+50	75	SELV	305x30x18.2	152
LT-75-12	220-240	75	12	0-6.25	0.95	90	<0.5	-20...+40	90	SELV	305x30x18.2	152
LT-75-24	220-240	75	24	0-3.125	0.95	90	<0.5	-20...+50	90	SELV	305x30x18.2	152
LT-100-12	220-240	100	12	0-8.34	0.95	91	<0.5	-20...+50	90	SELV	312x30x18.2	152
LT-100-24	220-240	100	24	0-4.17	0.95	92	<0.5	-20...+45	90	SELV	312x30x18.2	152
LT-100-48	220-240	100	48	0-2.08	0.95	92	<0.5	-20...+45	90	SELV	312x30x18.2	152
LT-150-12	220-240	132	12	0-11	0.95	92	<0.5	-20...+45	85	SELV	335x30x21.6	235
LT-150-24	220-240	150	24	0-6.25	0.95	93	<0.5	-20...+45	80	SELV	335x30x21.6	235
LT-150-48	220-240	150	48	0-3.125	0.95	92	<0.5	-20...+45	85	SELV	335x30x21.6	235
LT-200-24	220-240	200	24	0-8.34	0.95	93	<0.5	-20...+45	90	SELV	335x30x21.6	330
LT-240-24	220-240	240	24	0-10	0.95	93	<0.5	-20...+45	90	SELV	357x32x22.5	350
LT-240-48	220-240	240	48	0-5	0.95	93	<0.5	-20...+45	90	SELV	357x32x22.5	350